Radio Occultation Results from MarCO, The First Interplanetary CubeSat Mission

Kamal Oudrhiri⁽¹⁾, Yu-Ming Yang⁽¹⁾, Paul Withers⁽²⁾, Dustin Buccino⁽¹⁾, Norman Lay⁽¹⁾, Paolo Tortora⁽³⁾, Daniel S Kahan⁽¹⁾, Joseph Lazio⁽¹⁾, Andrew Klesh⁽¹⁾, John Baker⁽¹⁾, Steve E Matousek⁽¹⁾, Susan Finley⁽¹⁾, Joel Krajewski⁽¹⁾, Serjik Zadourian⁽¹⁾

- (1) Jet Propulsion Laboratory, California Institute of Technology, Pasadena, CA, USA
- (2) Boston University, Boston, MA, USA
- (3) University of Bologna, Italy




Outline



- Introduction MarCO Mission
- MarCO Radio Communication
- MarCO Radio Occultation Performance Analysis
- Investigation of Future Planetary Science Missions using CubSats.
- Summary


Introduction – MarCO Mission





MarCO Radio Communication






Noise sources on the MarCO radio link include:

- Ground equipment:
 - Frequency and Timing System noise
 - Antenna mechanical noise
- Spacecraft equipment:
 - Auxiliary Oscillator Stability
 - Translator Noise
 - Spacecraft Pointing
- Propagation effects:
 - Plasma noise (from Sun)
 - o Earth Ionosphere delay
 - Earth troposphere noise


Dec. 12, 2019 4

Analysis of MarCO Radio Science Measurement Uncertainties





Operational Phase	Tracking Mode	STD (Hz)
InSight AEDL		
MarCO-B	2-way	0.005
MarCO-A	2-way	0.004
Radio Occultation		
MarCO-A	1-way	0.42



MarCO Radio Occultation Experiment




Time	e (UTC-ERT)	Event	. 120
	14:15:00	Begin Open-Loop Recordings	400
	19:17:48	DSS-63 Acqusition	100 p
	19:53:09	InSight Landing	
	20:51:56	Turn Away from Earth-Point	90 F
	20:52:00 DSS-63 Loss of Signal		Socialization (*)
21:33:19 Geometric Occultation Ingress		Geometric Occultation Ingress	
,	23:43:07	Turn to Earth-Point	adr light 40 th
,	23:39:09	Geometric Occultation Egress	= 100 100
23:46:48 DSS-26 Acquisition, 1-Way		DSS-26 Acquisition, 1-Way	og ed and a second seco
00:48:10 DSS-26 Loss of Signal		DSS-26 Loss of Signal	-400 -200 0 200 400
	01:00:00	End Open-Loop Recordings	Seconds since A quisition (23:46:48)
35 - 30 - (25 -	*	+ + + + + + + + + + + + + + + + + + +	DSC Egress, 23:39 + DSS-26 + DSS-26
25 - 25 - 20 - 20 - 25 - 25 - 25 - 25 -	+ + Noise Floo	+	AOS, 2
10 - 5 - 0 -	Noise Floo	r ~ 12 dB-Hz	


Simulation of MarCO Radio Occultation



Mars Ionosphere Electron Density Profiles







MarCO noise level is about ~0.004 Hz and Allan deviation 4x10⁻¹³ (for 1s integration time) which is sensitive to Mars Atmosphere and Ionosphere Occultation.

Scientific Applications of CubeSat: Radio Science



Spacecraft	Tracking Mode	Allan Deviation (integration time 1s)
MarCO-A	2-way	4e-13
MarCO-B	2-way	4e-13
Voyager	2-way	3e-11
Huygens	2-way	1e-11
MRO	2-way	5e-13
Galileo Probe	2-way	5e-12
MGS	2-way	3e-13
Cassini	2-way	2e-13

Dec. 12, 2019

Summary and Future Work



- ➤ An assessment of the MarCO flyby and RO data indicates that the MarCO 2-way data has more stable frequency residual with a noise level about ~0.005 Hz and Allan deviation ~10⁻¹²(for 1s integration time). <u>Its</u> performance is in the same order of MRO 2 way data.
- Simulation result implies the 2-way MarCO radio signal could have been able to execute an ingress radio occultation of Mars and have a positive detection of the atmosphere and ionosphere.
- ➤ The assessment of frequency residual measurements derived from MarCO X-band radio links implies that the 1-way X-band data was not of the quality for Mars Radio Occultation.

Acknowledgments

This work was supported as a part of the work on MarCO Mission.



Contact Information:

Kamal Oudrhiri (supervisor), Planetary Radar & Radio Sciences Group, JPL Email: kamal.oudrhiri@jpl.nasa.gov

Dec. 12, 2019